

PATIO SEALER

SUITABLE FOR INDOOR & OUTDOOR
STONE AND CONCRETE

Seals and protects against staining
from water, oil-based dirt and grime.

ROB PARKER'S
BEST
Rob Parker



GENERAL PRODUCT DESCRIPTION

PATIO SEALER provides an optimum all-round protection for porous building materials. This single product provides water and oil repellent protection for walls, flooring and roofing.

Can be used inside and outdoors on both highly porous and low porosity materials eg. limestone, granite, sandstone, marble and slate and surfaces subject to high levels of foot traffic including pavements, pedestrian precincts, patios, swimming pool decks, stairways and car parking area.

A non film-forming surface impregnation, where the surface remains permeable to air and water vapour. Does not alter the surface colour. Aesthetics and composition of the treated material remains unchanged. A treated surface becomes UV-resistant and will not discolour with age.

ADVANTAGES AND CHARACTERISTICS

A surface treated with MULTI-SURFACE SEALER will wear better over time and be easier to maintain. This treatment also offers a solution to the main causes of deterioration, like atmospheric pollution, grease-type dirt, penetration of liquids, graffiti and also makes chewing-gum easier to remove.

Water-borne fluoropolymer dispersion.

DIRECTIONS FOR USE

Shake the container well before use.

Ensure the surface to be treated is clean, dust-free and visually dry before application.

Surface moisture content needs to be a <5% up to a depth of 1cm.

Use neat ; do not dilute.

Apply using a low-pressure sprayer, roller or brush.

The treated surface has to be applied to saturation, either in one application or in two applications 'wet-on-wet'.

On vertical surfaces, apply from the bottom up taking care in avoiding the product to 'run'.

Drying time: 24 hours.

For the optimum performance: allow 5 to 7 days (avoid high pressure, steam cleaning and graffiti removal until this period has elapsed).

Clean tools and equipment immediately after use with water.

PACKAGING

Available in 1 and 5 litre containers.

STORAGE

Keep product in a cool, dry place. Keep away from extreme cold and do not store in conditions below 5° C.

In an unopened container, stored in the recommended conditions the product shelf life is 12 months.

[MORE INFORMATION >>](#)

RECOMMENDATIONS FOR USE

Remove atmospheric pollution-related soiling from all surfaces to be treated before starting the application.

Must be shaken before use and only used when the ambient surface and air temperature is > 5°C.

Do not apply during rainy or very hot weather. If there is likely to be rain in the next 4 hours, wait until a dry period occurs.

Do not dilute or mix with any other product.

It is always advisable to carry out a trial application first to ascertain best means of application as well as calculating an actual coverage rate.

APPLICATION RATE

This will depend on the materials porosity. This guide indicates approximate rates only:

MATERIAL	APPROXIMATE RATE
Granite	Up to 18 m ² /litre
Marble	Up to 12m ² /litre
Sandstone	Up to 10m ² /litre
Limestone	Between 1-3 m ² /litre
Terracotta	Up to 5 m ² /litre
Cast Concrete	Up to 5 m ² /litre
Polished Concrete	Up to 10 m ² /litre
Interlocking Paving Stones	Up to 7 m ² /litre

TECHNICAL DATA

Physical state at 20° C: Liquid

Appearance: Pale straw colour

Odour: None

pH: 6 ± 0.5

Boiling point: 100° C

Density: 1.0kg/L

Solubility in water: Fully soluble

Flash point: N/A

VOC: 0g/L

HEALTH AND SAFETY PRECAUTIONS

Respiratory Protection: Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.

Hand Protection: None required

Skin Protection: No special protective clothing or skin protection is required under normal conditions of use

Eye Protection: If there is a real risk of splashing, wear protective goggles

If swallowed: do not induce vomiting. Contact a doctor or a specialist

KEEP OUT OF THE REACH OF CHILDREN

TECHNICAL ASSISTANCE

Stoneworld (Oxfordshire) Views Farm, Great Milton, Oxon. OX44 7NW.

T: 01844 279274. E: sales@robparkersbest.co.uk. www.robparkersbest.co.uk

Important: The contents of this document are the result of experience gained with this product. The company cannot be held liable for its use in individual cases. For more information, please see the Material Safety Data Sheet.